



C900



PipeLife Jetstream manufactures AWWA C900 product family which includes 4" to 12" C.I OD pipes. AWWA C900 standards include all specifications relating to the production and testing of C900 pipes. In three pressure ratings of DR25, DR 18 and DR25.

Our C900 is suitable for the transmission and distribution of water. PipeLife Jetstream carries various certifications from NSF International (NSF), Underwriters Laboratories (UL) and Factory Mutual (FM).

PipeLife Jetstream uses compound according to ASTM D1784—12454 as well as integral gasket joints according to ASTM F477 and ASTM D3139. To aid in the installation of PipeLife Jetstream's C900, each spigot end is beveled and includes a depth mark for insertion guidance.

DR 14 Pressure Ratings are: UL 305 and FM 200 PSI both at 73.4 degrees

Size	Outside Diameter	Minimum Wall Thickness	Weight LBS/Foot	Pieces per Pallet	Order Units	*Optional Colors
4	4.80	0.343	3.22	36	2.4	Yes
6	6.90	0.493	6.70	18	3	Yes
8	9.05	0.646	11.55	10	2.4	Yes
10	11.10	0.793	17.46	4	2	Yes
12	13.20	0.943	24.75	4/3	4	Yes

12454 (Type 1, Grade 1, PVC 1120) Material

DR 18 Pressure Ratings are: UL 235 PSI and FM 150 PSI both at 73.4 degrees

Size	Outside Diameter	Minimum Wall Thickness	Weight LBS/Foot	Pieces per Pallet	Order Units	*Optional Colors
4	4.800	0.267	2.55	36	2.4	Yes
6	6.900	0.383	5.29	18	3	Yes
8	9.050	0.503	9.15	10	2.4	Yes
10	11.100	0.617	13.82	4	2	Yes
12	13.200	0.733	19.56	4/3	4	Yes

DR 25 Pressure Ratings are: UL 165 PSI

Size	Outside Diameter	Minimum Wall Thickness	Weight LBS/Foot	Pieces per Pallet	Order Units	*Optional Colors
4	4.800	0.192	1.87	36	2.4	Yes
6	6.900	0.276	3.90	18	3	Yes
8	9.050	0.362	6.69	10	2.4	Yes
10	11.100	0.444	10.16	4	2	Yes
12	13.200	0.528	14.43	4	4	Yes